

## DABO® screw TKR-4-4.8



### Application range

- > To secure roofing membrane and insulating material to sheet steel substructures  $\geq 1.5 \text{ mm} \leq 4.0 \text{ mm}$
- > For combination with stress plates
- > For new buildings

### Properties

- > Case-hardened steel
- > With bugle head
- > High-grade coating to improve the corrosion protection (15 Kesternich cycles, DIN 50018)
- > Can be delivered belted for installation tool EOCSET or pre-assembled and belted with stress plate HTK-2G for installation tool ECOSSET HTK

### Length determination (minimum lengths)

Sheet steel	Total panel thickness + 20 mm
Timber	Total panel thickness + 30 mm

### Cross references

Stress plate HTV 82/40 TK  
 Stress plate HTV 82/40 F  
 Stress plate HTV 40 RU  
 Flat roof profile FP  
 Stress plate HTK-S  
 Stress plate HTK-2G 50  
 Stress plate EcoTek 50  
 Bit cross recess



EJOT® installation tool ECOSSET available as rental equipment  
 Article number G000000076



EJOT® installation tool EOCSET available as rental equipment.  
 Article number G000000072

### Applications



### Technical specifications



### Certifications



### Product online



Order description	Length [mm]	Thread length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
TKR-4-4.8x70	70	56	500		3438070639	4061245012438
TKR-4-4.8x90	90	56	500		3438090639	4061245012421
TKR-4-4.8 x110	110	56	250		3438110639	4061245012414

### Compatibility acc. to ETA-07/0013

	HTV 82/40	HTE 82/40	HTV 82/40 TK	HTV 82/40 F	HTV 40 RU	HTK 2G 50xL	HTK 2G 75xL	EcoTek 50	HTK-S	Flat roof profile FP
<b>TKR-4-4.8</b>			•	•	•	•	•	•	•	•